HOUSE SUBSTITUTE FOR SENATE BILL NO. 274

A bill to amend 1949 PA 300, entitled "Michigan vehicle code,"

by amending section 719 (MCL 257.719), as amended by 2012 PA 282.

THE PEOPLE OF THE STATE OF MICHIGAN ENACT:

- 1 Sec. 719. (1) A vehicle unloaded or with load shall not exceed
- 2 a height of 13 feet 6 inches. The owner of a vehicle that collides
- 3 with a lawfully established bridge or viaduct is liable for all
- 4 damage and injury resulting from a collision caused by the height
- 5 of the vehicle, whether the clearance of the bridge or viaduct is
- 6 posted or not.
- 7 (2) Lengths described in this subsection shall be known as the
- 8 normal length maximum. Except as provided in subsection (3), the
- 9 following vehicles and combinations of vehicles shall not be

- 1 operated on a highway in this state in excess of these lengths:
- 2 (a) Subject to subsection (8), (9), any single vehicle: 40
- 3 feet; a crib vehicle on which logs are loaded lengthwise of the
- 4 vehicle: 42.5 feet; any single bus or motor home: 45 feet.
- **5** (b) Articulated buses: 65 feet.
- 6 (c) Notwithstanding any other provision of this section, a
- 7 combination of a truck and semitrailer or trailer, or a truck
- 8 tractor, semitrailer, and trailer, or truck tractor and semitrailer
- 9 or trailer, designed and used exclusively to transport assembled
- 10 motor vehicles or bodies, recreational vehicles, or boats: 65 feet.
- 11 A combination of a truck and semitrailer or trailer, or a truck
- 12 tractor, semitrailer, and trailer, or a truck tractor and
- 13 semitrailer or trailer designed and used to transport boats from
- 14 the manufacturer, or a stinger-steered combination: 75 feet. The
- 15 load on the combinations of vehicles described in this subdivision
- 16 may extend an additional 3 feet beyond the front and 4 feet beyond
- 17 the rear of the combinations of vehicles. Retractable extensions
- 18 used to support and secure the load that do not extend beyond the
- 19 allowable overhang for the front and rear shall not be included in
- 20 determining length of a loaded vehicle or vehicle combination.
- 21 (d) Truck tractor and semitrailer combinations: no overall
- 22 length, the semitrailer: 50 feet.
- (e) Truck and semitrailer or trailer: 59 feet.
- 24 (f) Except as provided in subdivision (g), truck tractor,
- 25 semitrailer, and trailer, or truck tractor and 2 semitrailers: 59
- **26** feet.
- 27 (g) A truck tractor, semitrailer, and trailer, or a truck

- 1 tractor and 2 semitrailers, in which no semitrailer or trailer is
- 2 more than 28-1/2 feet long: 65 feet. This subdivision only applies
- 3 while the vehicle is being used for a business purpose reasonably
- 4 related to picking up or delivering a load and only if each
- 5 semitrailer or trailer is equipped with a device or system capable
- 6 of mechanically dumping construction materials or dumping
- 7 construction materials by force of gravity.
- 8 (h) More than 1 motor vehicle, wholly or partially assembled,
- 9 in combination, utilizing 1 tow bar or 3 saddle mounts with full
- 10 mount mechanisms and utilizing the motive power of 1 of the
- 11 vehicles in combination: 55 feet.
- 12 (i) A recreational vehicle that has its own motive power, in
- 13 combination with a trailer: 65 feet or, if the operator of the
- 14 recreational vehicle has a group commercial motor vehicle
- 15 designation on his or her operator's or chauffeur's license, 75
- **16** feet.
- 17 (3) Notwithstanding subsection (2), the following vehicles and
- 18 combinations of vehicles shall not be operated on a designated
- 19 highway of this state in excess of these lengths:
- 20 (a) Truck tractor and semitrailer combinations: no overall
- 21 length limit, the semitrailer 53 feet. All semitrailers longer than
- 22 50 feet shall have a wheelbase of 37.5 to 40.5 feet plus or minus
- 23 0.5 feet, measured from the kingpin coupling to the center of the
- 24 rear axle or the center of the rear axle assembly. City, village,
- 25 or county authorities may prohibit stops of vehicles with a
- 26 semitrailer longer than 50 feet within their jurisdiction unless
- 27 the stop occurs along appropriately designated routes, or is

- 1 necessary for emergency purposes or to reach shippers, receivers,
- 2 warehouses, and terminals along designated routes.
- 3 (b) Truck and semitrailer or trailer combinations: 65 feet,
- 4 except that a person may operate a truck and semitrailer or trailer
- 5 designed and used to transport saw logs, pulpwood, and tree length
- 6 poles that does not exceed an overall length of 70 feet or a crib
- 7 vehicle and semitrailer or trailer designed and used to transport
- 8 saw logs that does not exceed an overall length of 75 feet. A crib
- 9 vehicle and semitrailer or trailer designed to and used to
- 10 transport saw logs shall not exceed a gross vehicle weight of
- 11 164,000 pounds. A person may operate a truck tractor and
- 12 semitrailer designed and used to transport saw logs, pulpwood, and
- 13 tree length wooden poles with a load overhang to the rear of the
- 14 semitrailer which does not exceed 6 feet if the semitrailer does
- 15 not exceed 50 feet in length.
- (c) Notwithstanding subsection $\frac{(4)(d)}{(5)(D)}$, a truck tractor
- 17 with a log slasher unit and a log saw unit: no overall limit if the
- 18 length of each unit does not exceed 28-1/2 feet, or the overall
- 19 length of the log slasher unit and the log saw unit, as measured
- 20 from the front of the first towed unit to the rear of the second
- 21 towed unit while the units are coupled together, does not exceed 58
- 22 feet. The coupling devices of the truck tractor and units set forth
- 23 in this subdivision shall meet the requirements established under
- 24 the motor carrier safety act of 1963, 1963 PA 181, MCL 480.11 to
- **25** 480.25.
- 26 (d) Truck tractor and 2 semitrailers, or truck tractor,
- 27 semitrailer, and trailer combinations: no overall length limit, if

- 1 the length of each semitrailer or trailer does not exceed 28-1/2
- 2 feet each, or the overall length of the semitrailer and trailer, or
- 3 2 semitrailers as measured from the front of the first towed unit
- 4 to the rear of the second towed unit while the units are coupled
- 5 together does not exceed 58 feet.
- 6 (e) More than 1 motor vehicle, wholly or partially assembled,
- 7 in combination, utilizing 1 tow bar or 3 saddle mounts with full
- 8 mount mechanisms and utilizing the motive power of 1 of the
- 9 vehicles in combination: 75-97 feet.
- 10 (f) Truck tractor and lowboy semitrailer combinations: no
- 11 maximum overall length, if the lowboy semitrailer does not exceed
- 12 59 feet, except as otherwise permitted under this subdivision. A
- 13 lowboy semitrailer wheelbase shall not exceed 55 feet as measured
- 14 from the kingpin coupling to the center of the rear axle. A lowboy
- 15 semitrailer more than 59 feet in length shall not operate with more
- 16 than any combination of 4 axles on the lowboy unless an oversized
- 17 load permit is issued by the state transportation department or a
- 18 local authority with respect to highways under its jurisdiction. As
- 19 used in this subdivision, "lowboy semitrailer" means a flatbed
- 20 semitrailer with a depressed section that has the specific purpose
- 21 of being lowered and raised for loading and unloading.
- 22 (4) NOTWITHSTANDING ANY OTHER PROVISION OF THIS SECTION, A
- 23 COMBINATION OF A TRUCK AND SEMITRAILER, OR TRUCK TRACTOR AND
- 24 SEMITRAILER, USED EXCLUSIVELY TO TRANSPORT ASSEMBLED MOTOR VEHICLES
- 25 OR BODIES THAT HAVE A TRAILER LENGTH OF 53 FEET MAY HAVE A LOAD
- 26 THAT EXTENDS AN ADDITIONAL 3 FEET BEYOND THE FRONT OF THE TRAILER
- 27 AND 4 FEET BEYOND THE REAR OF THE TRAILER. RETRACTABLE EXTENSIONS

- 1 USED TO SUPPORT AND SECURE THE LOAD THAT DO NOT EXTEND BEYOND THE
- 2 ALLOWABLE OVERHANG FOR THE FRONT AND REAR SHALL NOT BE INCLUDED IN
- 3 DETERMINING LENGTH OF A LOADED VEHICLE OR VEHICLE COMBINATION. THE
- 4 TOTAL OVERALL LENGTH LOADED OF THE COMBINATION OF VEHICLES
- 5 DESCRIBED IN THIS SUBSECTION SHALL NOT EXCEED 79 FEET.
- 6 (5) (4) The following combinations and movements are
- 7 prohibited:
- 8 (a) A truck shall not haul more than 1 trailer or semitrailer,
- 9 and a truck tractor shall not haul more than 2 semitrailers or 1
- 10 semitrailer and 1 trailer in combination at any 1 time, except that
- 11 a farm tractor may haul 2 wagons or trailers, or garbage and refuse
- 12 haulers may, during daylight hours, haul up to 4 trailers for
- 13 garbage and refuse collection purposes, not exceeding in any
- 14 combination a total length of 55 feet and at a speed limit not to
- 15 exceed 15 miles per hour.
- 16 (b) A combination of vehicles or a vehicle shall not have more
- 17 than 11 axles, except when operating under a valid permit issued by
- 18 the state transportation department or a local authority with
- 19 respect to a highway under its jurisdiction.
- 20 (c) Any combination of vehicles not specifically authorized
- 21 under this section is prohibited.
- (d) Except as provided in subsection (3)(c), a combination of
- 23 2 semitrailers pulled by a truck tractor, unless each semitrailer
- 24 uses a fifth wheel connecting assembly that conforms to the
- 25 requirements of the motor carrier safety act of 1963, 1963 PA 181,
- 26 MCL 480.11 to 480.25.
- 27 (e) A vehicle or a combination of vehicles shall not carry a

- 1 load extending more than 3 feet beyond the front of the lead
- 2 vehicle.
- **3** (f) A vehicle described in subsections (2)(e) and (3)(e)
- 4 employing triple saddle mounts unless all wheels that are in
- 5 contact with the roadway have operating brakes.
- 6 (6) (5) All combinations of vehicles under this section shall
- 7 employ connecting assemblies and lighting devices that are in
- 8 compliance with the motor carrier safety act of 1963, 1963 PA 181,
- 9 MCL 480.11 to 480.25.
- 10 (7) (6) The total gross weight of a truck tractor,
- 11 semitrailer, and trailer combination or a truck tractor and 2
- 12 semitrailers combination that exceeds 59 feet in length shall not
- 13 exceed a ratio of 400 pounds per engine net horsepower delivered to
- 14 clutch or its equivalent specified in the handbook published by the
- 15 society SOCIETY of automotive engineers, inc. AUTOMOTIVE ENGINEERS,
- 16 INC. (SAE), 1977 edition.
- 17 (8) (7) A person who violates this section is responsible for
- 18 a civil infraction. The owner of the vehicle may be charged with a
- 19 violation of this section.
- 20 (9) $\frac{(8)}{}$ The provisions in subsections (2)(a) and (3)(b)
- 21 prescribing the length of a crib vehicle on which logs are loaded
- 22 lengthwise do not apply unless 23 USC 127(d) is amended to allow
- 23 crib vehicles carrying logs to be loaded as described in this
- 24 section.
- 25 (10) $\frac{(9)}{}$ As used in this section:
- 26 (a) "Designated highway" means a highway approved by the state
- 27 transportation department or a local authority with respect to a

- 1 highway under its jurisdiction.
- 2 (b) "Length" means the total length of a vehicle, or
- 3 combination of vehicles, including any load the vehicle is
- 4 carrying. Length does not include devices described in 23 CFR
- **5** 658.16 and 23 CFR part 658, appendix d, 23 CFR 658.16 and 23 CFR
- 6 part 658, appendix d, as on file with the secretary of state are
- 7 adopted by reference. A safety or energy conservation device shall
- 8 be excluded from a determination of length only if it is not
- 9 designed or used for the carrying of cargo, freight, or equipment.
- 10 Semitrailers and trailers shall be measured from the front vertical
- 11 plane of the foremost transverse load supporting structure to the
- 12 rearmost transverse load supporting structure. Vehicle components
- 13 not excluded by law shall be included in the measurement of the
- 14 length, height, and width of the vehicle.
- 15 (c) "Stinger-steered combinations" means a truck tractor and
- 16 semitrailer combination in which the fifth wheel is located on a
- 17 drop frame located behind and below the rearmost axle of the power
- **18** unit.
- 19 Enacting section 1. This amendatory act takes effect 90 days
- 20 after the date it is enacted into law.