SUBSTITUTE FOR

SENATE BILL NO. 274

A bill to amend 1949 PA 300, entitled "Michigan vehicle code,"

by amending section 719 (MCL 257.719), as amended by 2012 PA 282.

THE PEOPLE OF THE STATE OF MICHIGAN ENACT:

- 1 Sec. 719. (1) A vehicle unloaded or with load shall not exceed
- 2 a height of 13 feet 6 inches. The owner of a vehicle that collides
- 3 with a lawfully established bridge or viaduct is liable for all
- 4 damage and injury resulting from a collision caused by the height
- 5 of the vehicle, whether the clearance of the bridge or viaduct is
- 6 posted or not.
- 7 (2) Lengths described in this subsection shall be known as the
- 8 normal length maximum. Except as provided in subsection (3), the
- 9 following vehicles and combinations of vehicles shall not be
- 10 operated on a highway in this state in excess of these lengths:
- 11 (a) Subject to subsection (8), (9), any single vehicle: 40

- 1 feet; a crib vehicle on which logs are loaded lengthwise of the
- 2 vehicle: 42.5 feet; any single bus or motor home: 45 feet.
- 3 (b) Articulated buses: 65 feet.
- 4 (c) Notwithstanding any other provision of this section, a
- 5 combination of a truck and semitrailer or trailer, or a truck
- 6 tractor, semitrailer, and trailer, or truck tractor and semitrailer
- 7 or trailer, designed and used exclusively to transport assembled
- 8 motor vehicles or bodies, recreational vehicles , or boats: 65
- 9 feet. A combination of a truck and semitrailer or trailer, or a
- 10 truck tractor, semitrailer, and trailer, or a truck tractor and
- 11 semitrailer or trailer designed and used to transport boats from
- 12 the manufacturer, or a stinger-steered combination: 75 feet. The
- 13 load on the combinations of vehicles described in this subdivision
- 14 may extend an additional 3 feet beyond the front and 4 feet beyond
- 15 the rear of the combinations of vehicles. Retractable extensions
- 16 used to support and secure the load that do not extend beyond the
- 17 allowable overhang for the front and rear shall not be included in
- 18 determining length of a loaded vehicle or vehicle combination.
- 19 (d) Truck tractor and semitrailer combinations: no overall
- 20 length, the semitrailer: 50 feet.
- 21 (e) Truck and semitrailer or trailer: 59 feet.
- (f) Except as provided in subdivision (g), truck tractor,
- 23 semitrailer, and trailer, or truck tractor and 2 semitrailers: 59
- **24** feet.
- 25 (g) A truck tractor, semitrailer, and trailer, or a truck
- 26 tractor and 2 semitrailers, in which no semitrailer or trailer is
- 27 more than 28-1/2 feet long: 65 feet. This subdivision only applies

- 1 while the vehicle is being used for a business purpose reasonably
- 2 related to picking up or delivering a load and only if each
- 3 semitrailer or trailer is equipped with a device or system capable
- 4 of mechanically dumping construction materials or dumping
- 5 construction materials by force of gravity.
- 6 (h) More than 1 motor vehicle, wholly or partially assembled,
- 7 in combination, utilizing 1 tow bar or 3 saddle mounts with full
- 8 mount mechanisms and utilizing the motive power of 1 of the
- 9 vehicles in combination: 55 feet.
- 10 (i) A recreational vehicle that has its own motive power, in
- 11 combination with a trailer: 65 feet or, if the operator of the
- 12 recreational vehicle has a group commercial motor vehicle
- designation on his or her operator's or chauffeur's license, 75
- 14 feet.
- 15 (3) Notwithstanding subsection (2), the following vehicles and
- 16 combinations of vehicles shall not be operated on a designated
- 17 highway of this state in excess of these lengths:
- 18 (a) Truck tractor and semitrailer combinations: no overall
- 19 length limit, the semitrailer 53 feet. All semitrailers longer than
- 20 50 feet shall have a wheelbase of 37.5 to 40.5 feet plus or minus
- 21 0.5 feet, measured from the kingpin coupling to the center of the
- 22 rear axle or the center of the rear axle assembly. City, village,
- 23 or county authorities may prohibit stops of vehicles with a
- 24 semitrailer longer than 50 feet within their jurisdiction unless
- 25 the stop occurs along appropriately designated routes, or is
- 26 necessary for emergency purposes or to reach shippers, receivers,
- 27 warehouses, and terminals along designated routes.

- 1 (b) Truck and semitrailer or trailer combinations: 65 feet,
- 2 except that a person may operate a truck and semitrailer or trailer
- 3 designed and used to transport saw logs, pulpwood, and tree length
- 4 poles that does not exceed an overall length of 70 feet or a crib
- 5 vehicle and semitrailer or trailer designed and used to transport
- 6 saw logs that does not exceed an overall length of 75 feet. A crib
- 7 vehicle and semitrailer or trailer designed to and used to
- 8 transport saw logs shall not exceed a gross vehicle weight of
- 9 164,000 pounds. A person may operate a truck tractor and
- 10 semitrailer designed and used to transport saw logs, pulpwood, and
- 11 tree length wooden poles with a load overhang to the rear of the
- 12 semitrailer which does not exceed 6 feet if the semitrailer does
- 13 not exceed 50 feet in length.
- 14 (c) Notwithstanding subsection $\frac{(4)(d)}{(5)(D)}$, a truck tractor
- 15 with a log slasher unit and a log saw unit: no overall limit if the
- 16 length of each unit does not exceed 28-1/2 feet, or the overall
- 17 length of the log slasher unit and the log saw unit, as measured
- 18 from the front of the first towed unit to the rear of the second
- 19 towed unit while the units are coupled together, does not exceed 58
- 20 feet. The coupling devices of the truck tractor and units set forth
- 21 in this subdivision shall meet the requirements established under
- 22 the motor carrier safety act of 1963, 1963 PA 181, MCL 480.11 to
- **23** 480.25.
- 24 (d) Truck tractor and 2 semitrailers, or truck tractor,
- 25 semitrailer, and trailer combinations: no overall length limit, if
- 26 the length of each semitrailer or trailer does not exceed 28-1/2
- 27 feet each, or the overall length of the semitrailer and trailer, or

- 1 2 semitrailers as measured from the front of the first towed unit
- 2 to the rear of the second towed unit while the units are coupled
- 3 together does not exceed 58 feet.
- 4 (e) More than 1 motor vehicle, wholly or partially assembled,
- 5 in combination, utilizing 1 tow bar or 3 saddle mounts with full
- 6 mount mechanisms and utilizing the motive power of 1 of the
- 7 vehicles in combination: 75 97 feet.
- 8 (f) Truck tractor and lowboy semitrailer combinations: no
- 9 maximum overall length, if the lowboy semitrailer does not exceed
- 10 59 feet, except as otherwise permitted under this subdivision. A
- 11 lowboy semitrailer wheelbase shall not exceed 55 feet as measured
- 12 from the kingpin coupling to the center of the rear axle. A lowboy
- 13 semitrailer more than 59 feet in length shall not operate with more
- 14 than any combination of 4 axles on the lowboy unless an oversized
- 15 load permit is issued by the state transportation department or a
- 16 local authority with respect to highways under its jurisdiction. As
- 17 used in this subdivision, "lowboy semitrailer" means a flatbed
- 18 semitrailer with a depressed section that has the specific purpose
- 19 of being lowered and raised for loading and unloading.
- 20 (4) NOTWITHSTANDING ANY OTHER PROVISION OF THIS SECTION, A
- 21 COMBINATION OF A TRUCK AND SEMITRAILER, OR TRUCK TRACTOR AND
- 22 SEMITRAILER, USED EXCLUSIVELY TO TRANSPORT ASSEMBLED MOTOR VEHICLES
- 23 OR BODIES THAT HAVE A TRAILER LENGTH OF 53 FEET MAY HAVE A LOAD
- 24 THAT EXTENDS AN ADDITIONAL 3 FEET BEYOND THE FRONT OF THE TRAILER
- 25 AND 4 FEET BEYOND THE REAR OF THE TRAILER. RETRACTABLE EXTENSIONS
- 26 USED TO SUPPORT AND SECURE THE LOAD THAT DO NOT EXTEND BEYOND THE
- 27 ALLOWABLE OVERHANG FOR THE FRONT AND REAR SHALL NOT BE INCLUDED IN

- 1 DETERMINING LENGTH OF A LOADED VEHICLE OR VEHICLE COMBINATION. THE
- 2 TOTAL OVERALL LENGTH LOADED OF THE COMBINATION OF VEHICLES
- 3 DESCRIBED IN THIS SUBSECTION SHALL NOT EXCEED 79 FEET.
- 4 (5) (4) The following combinations and movements are
- 5 prohibited:
- 6 (a) A truck shall not haul more than 1 trailer or semitrailer,
- 7 and a truck tractor shall not haul more than 2 semitrailers or 1
- 8 semitrailer and 1 trailer in combination at any 1 time, except that
- 9 a farm tractor may haul 2 wagons or trailers, or garbage and refuse
- 10 haulers may, during daylight hours, haul up to 4 trailers for
- 11 garbage and refuse collection purposes, not exceeding in any
- 12 combination a total length of 55 feet and at a speed limit not to
- 13 exceed 15 miles per hour.
- 14 (b) A combination of vehicles or a vehicle shall not have more
- 15 than 11 axles, except when operating under a valid permit issued by
- 16 the state transportation department or a local authority with
- 17 respect to a highway under its jurisdiction.
- 18 (c) Any combination of vehicles not specifically authorized
- 19 under this section is prohibited.
- 20 (d) Except as provided in subsection (3)(c), a combination of
- 21 2 semitrailers pulled by a truck tractor, unless each semitrailer
- 22 uses a fifth wheel connecting assembly that conforms to the
- 23 requirements of the motor carrier safety act of 1963, 1963 PA 181,
- 24 MCL 480.11 to 480.25.
- 25 (e) A vehicle or a combination of vehicles shall not carry a
- 26 load extending more than 3 feet beyond the front of the lead
- 27 vehicle.

- 1 (f) A vehicle described in subsections (2)(e) and (3)(e)
- 2 employing triple saddle mounts unless all wheels that are in
- 3 contact with the roadway have operating brakes.
- 4 (6) (5) All combinations of vehicles under this section shall
- 5 employ connecting assemblies and lighting devices that are in
- 6 compliance with the motor carrier safety act of 1963, 1963 PA 181,
- 7 MCL 480.11 to 480.25.
- 8 (7) (6) The total gross weight of a truck tractor,
- 9 semitrailer, and trailer combination or a truck tractor and 2
- 10 semitrailers combination that exceeds 59 feet in length shall not
- 11 exceed a ratio of 400 pounds per engine net horsepower delivered to
- 12 clutch or its equivalent specified in the handbook published by the
- 13 society SOCIETY of automotive engineers, inc. AUTOMOTIVE ENGINEERS,
- **14 INC.** (SAE), 1977 edition.
- 15 (8) (7) A person who violates this section is responsible for
- 16 a civil infraction. The owner of the vehicle may be charged with a
- 17 violation of this section.
- 18 (9) (8) The provisions in subsections (2) (a) and (3) (b)
- 19 prescribing the length of a crib vehicle on which logs are loaded
- 20 lengthwise do not apply unless 23 USC 127(d) is amended to allow
- 21 crib vehicles carrying logs to be loaded as described in this
- 22 section.
- 23 (10) $\frac{(9)}{}$ As used in this section:
- 24 (a) "Designated highway" means a highway approved by the state
- 25 transportation department or a local authority with respect to a
- 26 highway under its jurisdiction.
- (b) "Length" means the total length of a vehicle, or

- 1 combination of vehicles, including any load the vehicle is
- 2 carrying. Length does not include devices described in 23 CFR
- 3 658.16 and 23 CFR part 658, appendix d, 23 CFR 658.16 and 23 CFR
- 4 part 658, appendix d, as on file with the secretary of state are
- 5 adopted by reference. A safety or energy conservation device shall
- 6 be excluded from a determination of length only if it is not
- 7 designed or used for the carrying of cargo, freight, or equipment.
- 8 Semitrailers and trailers shall be measured from the front vertical
- 9 plane of the foremost transverse load supporting structure to the
- 10 rearmost transverse load supporting structure. Vehicle components
- 11 not excluded by law shall be included in the measurement of the
- 12 length, height, and width of the vehicle.
- 13 (c) "Stinger-steered combinations" means a truck tractor and
- 14 semitrailer combination in which the fifth wheel is located on a
- 15 drop frame located behind and below the rearmost axle of the power
- **16** unit.
- 17 Enacting section 1. This amendatory act takes effect 90 days
- 18 after the date it is enacted into law.