

**SUBSTITUTE FOR
SENATE BILL NO. 582**

A bill to amend 1949 PA 300, entitled
"Michigan vehicle code,"
by amending section 719 (MCL 257.719), as amended by 2009 PA 37.

THE PEOPLE OF THE STATE OF MICHIGAN ENACT:

1 Sec. 719. (1) A vehicle unloaded or with load shall not exceed
2 a height of 13 feet 6 inches. The owner of a vehicle that collides
3 with a lawfully established bridge or viaduct is liable for all
4 damage and injury resulting from a collision caused by the height
5 of the vehicle, whether the clearance of the bridge or viaduct is
6 posted or not.

7 (2) Lengths described in this subsection shall be known as the
8 normal length maximum. Except as provided in subsection (3), the
9 following vehicles and combinations of vehicles shall not be
10 operated on a highway in this state in excess of these lengths:

11 (a) Subject to subsection (8), any single vehicle: 40 feet; a

1 crib vehicle on which logs are loaded lengthwise of the vehicle:
2 42.5 feet; any single bus or motor home: 45 feet.

3 (b) Articulated buses: 65 feet.

4 (c) Notwithstanding any other provision of this section, a
5 combination of a truck and semitrailer or trailer, or a truck
6 tractor, semitrailer, and trailer, or truck tractor and semitrailer
7 or trailer, designed and used exclusively to transport assembled
8 motor vehicles or bodies, recreational vehicles, or boats, that
9 does not exceed a length of 65 feet. Stinger-steered combinations
10 shall not exceed a length of 75 feet. The load on the combinations
11 of vehicles described in this subdivision may extend an additional
12 3 feet beyond the front and 4 feet beyond the rear of the
13 combinations of vehicles. Retractable extensions used to support
14 and secure the load that do not extend beyond the allowable
15 overhang for the front and rear shall not be included in
16 determining length of a loaded vehicle or vehicle combination.

17 (d) Truck tractor and semitrailer combinations: no overall
18 length, the semitrailer not to exceed 50 feet.

19 (e) Truck and semitrailer or trailer: 59 feet.

20 (f) Except as provided in subdivision (g), truck tractor,
21 semitrailer, and trailer, or truck tractor and 2 semitrailers: 59
22 feet.

23 (g) A truck tractor, semitrailer, and trailer, or a truck
24 tractor and 2 semitrailers, in which no semitrailer or trailer is
25 more than 28-1/2 feet long: 65 feet. This subdivision only applies
26 while the vehicle is being used for a business purpose reasonably
27 related to picking up or delivering a load and only if each

1 semitrailer or trailer is equipped with a device or system capable
2 of mechanically dumping construction materials or dumping
3 construction materials by force of gravity.

4 (h) More than 1 motor vehicle, wholly or partially assembled,
5 in combination, utilizing 1 tow bar or 3 saddle mounts with full
6 mount mechanisms and utilizing the motive power of 1 of the
7 vehicles in combination, not to exceed 55 feet.

8 (3) Notwithstanding subsection (2), the following vehicles and
9 combinations of vehicles shall not be operated on a designated
10 highway of this state in excess of these lengths:

11 (a) Truck tractor and semitrailer combinations: no overall
12 length limit, the semitrailer not to exceed 53 feet. All
13 semitrailers longer than 50 feet shall have a wheelbase of 37.5 to
14 40.5 feet plus or minus 0.5 feet, measured from the kingpin
15 coupling to the center of the rear axle or the center of the rear
16 axle assembly. A semitrailer with a length longer than 50 feet
17 shall not operate with more than 3 axles on the semitrailer. City,
18 village, or county authorities may prohibit stops of vehicles with
19 a semitrailer longer than 50 feet within their jurisdiction unless
20 the stop occurs along appropriately designated routes, or is
21 necessary for emergency purposes or to reach shippers, receivers,
22 warehouses, and terminals along designated routes.

23 (b) Truck and semitrailer or trailer combinations: 65 feet,
24 except that a person may operate a truck and semitrailer or trailer
25 designed and used to transport saw logs, pulpwood, and tree length
26 poles that does not exceed an overall length of 70 feet or a crib
27 vehicle and semitrailer or trailer designed and used to transport

1 saw logs that does not exceed an overall length of 75 feet. A crib
2 vehicle and semitrailer or trailer designed to and used to
3 transport saw logs shall not exceed a gross vehicle weight of
4 164,000 pounds. A person may operate a truck tractor and
5 semitrailer designed and used to transport saw logs, pulpwood, and
6 tree length wooden poles with a load overhang to the rear of the
7 semitrailer which does not exceed 6 feet if the semitrailer does
8 not exceed 50 feet in length.

9 (c) Notwithstanding subsection (4)(d), a truck tractor with a
10 log slasher unit and a log saw unit: no overall limit if the length
11 of each unit does not exceed 28-1/2 feet, or the overall length of
12 the log slasher unit and the log saw unit, as measured from the
13 front of the first towed unit to the rear of the second towed unit
14 while the units are coupled together, does not exceed 58 feet. The
15 coupling devices of the truck tractor and units set forth in this
16 subdivision shall meet the requirements established under the motor
17 carrier safety act of 1963, 1963 PA 181, MCL 480.11 to 480.25.

18 (d) Truck tractor and 2 semitrailers, or truck tractor,
19 semitrailer, and trailer combinations: no overall length limit, if
20 the length of each semitrailer or trailer does not exceed 28-1/2
21 feet each, or the overall length of the semitrailer and trailer, or
22 2 semitrailers as measured from the front of the first towed unit
23 to the rear of the second towed unit while the units are coupled
24 together does not exceed 58 feet.

25 (e) More than 1 motor vehicle, wholly or partially assembled,
26 in combination, utilizing 1 tow bar or 3 saddle mounts with full
27 mount mechanisms and utilizing the motive power of 1 of the

1 vehicles in combination, not to exceed 75 feet.

2 (F) TRUCK TRACTOR AND LOWBOY SEMITRAILER COMBINATIONS: NO
3 MAXIMUM OVERALL LENGTH, IF THE LOWBOY SEMITRAILER DOES NOT EXCEED
4 59 FEET, EXCEPT AS OTHERWISE PERMITTED UNDER THIS SUBDIVISION. A
5 LOWBOY SEMITRAILER WHEELBASE SHALL NOT EXCEED 55 FEET AS MEASURED
6 FROM THE KINGPIN COUPLING TO THE CENTER OF THE REAR AXLE. A LOWBOY
7 SEMITRAILER MORE THAN 59 FEET IN LENGTH SHALL NOT OPERATE WITH MORE
8 THAN ANY COMBINATION OF 4 AXLES ON THE LOWBOY UNLESS AN OVERSIZED
9 LOAD PERMIT IS ISSUED BY THE STATE TRANSPORTATION DEPARTMENT OR A
10 LOCAL AUTHORITY WITH RESPECT TO HIGHWAYS UNDER ITS JURISDICTION. AS
11 USED IN THIS SUBDIVISION, "LOWBOY SEMITRAILER" MEANS A FLATBED
12 SEMITRAILER WITH A DEPRESSED SECTION THAT HAS THE SPECIFIC PURPOSE
13 OF BEING LOWERED AND RAISED FOR LOADING AND UNLOADING.

14 (4) The following combinations and movements are prohibited:

15 (a) A truck shall not haul more than 1 trailer or semitrailer,
16 and a truck tractor shall not haul more than 2 semitrailers or 1
17 semitrailer and 1 trailer in combination at any 1 time, except that
18 a farm tractor may haul 2 wagons or trailers, or garbage and refuse
19 haulers may, during daylight hours, haul up to 4 trailers for
20 garbage and refuse collection purposes, not exceeding in any
21 combination a total length of 55 feet and at a speed limit not to
22 exceed 15 miles per hour.

23 (b) A combination of vehicles or a vehicle shall not have more
24 than 11 axles, except when operating under a valid permit issued by
25 the state transportation department or a local authority with
26 respect to a highway under its jurisdiction.

27 (c) Any combination of vehicles not specifically authorized

1 under this section is prohibited.

2 (d) Except as provided in subsection (3)(c), a combination of
3 2 semitrailers pulled by a truck tractor, unless each semitrailer
4 uses a fifth wheel connecting assembly that conforms to the
5 requirements of the motor carrier safety act of 1963, 1963 PA 181,
6 MCL 480.11 to 480.25.

7 (e) A vehicle or a combination of vehicles shall not carry a
8 load extending more than 3 feet beyond the front of the lead
9 vehicle.

10 (f) A vehicle described in subsections (2)(e) and (3)(e)
11 employing triple saddle mounts unless all wheels that are in
12 contact with the roadway have operating brakes.

13 (5) All combinations of vehicles under this section shall
14 employ connecting assemblies and lighting devices that are in
15 compliance with the motor carrier safety act of 1963, 1963 PA 181,
16 MCL 480.11 to ~~480.22~~ **480.25**.

17 (6) The total gross weight of a truck tractor, semitrailer,
18 and trailer combination or a truck tractor and 2 semitrailers
19 combination that exceeds 59 feet in length shall not exceed a ratio
20 of 400 pounds per engine net horsepower delivered to clutch or its
21 equivalent specified in the handbook published by the society of
22 automotive engineers, inc. (SAE), 1977 edition.

23 (7) A person who violates this section is responsible for a
24 civil infraction. The owner of the vehicle may be charged with a
25 violation of this section.

26 (8) The provisions in subsections (2)(a) and (3)(b)
27 prescribing the length of a crib vehicle on which logs are loaded

lengthwise do not apply unless ~~section 127(d) of title 23 of the~~
~~United States Code, 23 USC 127,~~ **23 USC 127(D)** is amended to allow
crib vehicles carrying logs to be loaded as described in this
section.

(9) As used in this section:

(a) "Designated highway" means a highway approved by the state
transportation department or a local authority with respect to a
highway under its jurisdiction.

(b) "Length" means the total length of a vehicle, or
combination of vehicles, including any load the vehicle is
carrying. Length does not include devices described in 23 CFR
658.16 and 23 CFR part 658, appendix d. 23 CFR 658.16 and 23 CFR
part 658, appendix d, as on file with the secretary of state are
adopted by reference. A safety or energy conservation device shall
be excluded from a determination of length only if it is not
designed or used for the carrying of cargo, freight, or equipment.
Semitrailers and trailers shall be measured from the front vertical
plane of the foremost transverse load supporting structure to the
rearmost transverse load supporting structure. Vehicle components
not excluded by law shall be included in the measurement of the
length, height, and width of the vehicle.

(c) "Stinger-steered combinations" means a truck tractor and
semitrailer combination in which the fifth wheel is located on a
drop frame located behind and below the rearmost axle of the power
unit.